

(12) United States Patent

Burbank et al.

US 9,636,444 B2

(45) Date of Patent:

(10) Patent No.:

May 2, 2017

(54) FILTRATION SYSTEM FOR PREPARATION OF FLUIDS FOR MEDICAL APPLICATIONS

(71) Applicant: NXSTAGE MEDICAL, INC.,

Lawrence, MA (US)

Inventors: Jeffrey H. Burbank, Boxford, MA

(US); James M. Brugger, Newburyport, MA (US)

(73) Assignee: NXSTAGE MEDICAL, INC.,

Lawrence, MA (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 404 days.

(21) Appl. No.: 13/861,172

(22)Filed: Apr. 11, 2013

(65)**Prior Publication Data**

US 2013/0228505 A1 Sep. 5, 2013

Related U.S. Application Data

(63) Continuation of application No. 12/296,415, filed as application No. PCT/US2007/066251 on Apr. 9, 2007, now Pat. No. 8,469,331.

(Continued)

(51) Int. Cl. A61M 1/16

(2006.01)(2006.01)

A61J 1/14 (Continued)

(52) U.S. Cl.

CPC A61M 1/1656 (2013.01); A61J 1/05 $(2013.01); \textit{A61J 1/1468} \ (2015.05); \textit{A61J}$

1/1475 (2013.01);

(Continued)

Field of Classification Search

CPC A61M 1/1656; A61M 1/28; A61M 5/1408; A61M 5/145; A61M 39/288;

(Continued)

(56)References Cited

U.S. PATENT DOCUMENTS

5/1960 Trace A61M 1/0013

128/DIG, 24

2,995,334 A 8/1961 Henderson et al.

(Continued)

FOREIGN PATENT DOCUMENTS

8305713 12/1985 DE DE 19704564 8/1998

(Continued)

OTHER PUBLICATIONS

Pall Corporation, "Selection Guide: Separation Products for Centrifugal and Tangential Flow Filtration", Retrieved from http:// www.pall.com/main/laboratory/literature-library-details.page?id=7046 on Jul. 7, 2015.*

(Continued)

Primary Examiner — Katherine Zalasky Assistant Examiner — Benjamin Lebron (74) Attorney, Agent, or Firm — Potomac Law Group, PLLC; Mark Catan

ABSTRACT

Systems, methods, and devices for preparation of purified water and medicaments for various uses including blood treatment are described. Methods, devices, and systems for creating multiple-treatment batches are described. For example, a medicament fluid circuit can include a container with an interior chamber. The container can have a fluid filling port and a fluid extraction port. Both ports can be connected to the interior chamber. The filling port can have two sterilizing filters, each of which has a membrane. The sterilizing filters can be connected in series the membranes are separated by a distance of at least 0.5 cm. A first of the sterilizing filters can have a sealed inlet. The fluid extraction port can be sealed.

13 Claims, 28 Drawing Sheets

